

LVT CLICK 30

TECHNICAL DATA

TECHNICAL DATA	STANDARD	STARFLOOR CLICK 30
CLASSIFICATION		
CE Marking		EN 14041
Classification	EN 10582 EN ISO 10874	Heterogeneous Compact Resilient Floorcovering Domestic: 23 Commercial: 31
Wear layer binder content	EN ISO 10582	Type I
TECHNICAL CHARACTERISTICS		
Surface Treatment		Topcoat PU
Total thickness	EN ISO 24346	4,5 mm
Wear layer thickness	EN ISO 24340	0,30 mm
Total weight	EN ISO 23997	8kg/m ²
Installation Method		Click
Locking system		2G/1PFD
PERFORMANCES FOR CE MARKING		
DoP Number		0197-0054-DOP-2019-03
Slip resistance	EN 13893	$\mu \geq 0,30$
Reaction to fire	EN 13501-1	B _{fl} -s1 loose laid on concrete
Thermal resistance	EN ISO 10456	0.04 m ² K/W
Electrical Resistance	EN 1081	> 10 ⁹ Ohm
TECHNICAL PERFORMANCES		
Impact sound reduction	NF EN ISO 717 / 2	$\Delta L_w = 3$ dB
Electrostatical propensity	EN 1815	<2 kV on concrete
Slip resistance	DIN 51130	R9
Castor chair effect	ISO 4918	No damage
Furniture leg	EN 424	No damage
Residual Indentation	EN ISO 24343-1	$\leq 0,10$ mm
Chemical resistance	EN ISO 26987	Not affected (0)
Underfloor heating		Yes, maximum 27°C
Curl resultant to heat	EN ISO 23999	≤ 1 mm
Dimensional stability	EN ISO 23999	$\leq 0,10$ %
ENVIRONMENTAL PERFORMANCES		
Phthalate content		Phthalate free
Total VOC emissions after 28 days	ISO 16000-9	$\leq 10\mu\text{g}/\text{m}^3$
DIMENSIONS		
Tiles		60,1 x 32,38 cm = 9/box = 1,75 m ² /box
Plank		121,1 x 19,05 cm = 7/box = 1,61 m ² /box
OTHER		
Noise level index	NF S31-074	Class C ($L_{n,e,w} < 85$ dB)
Light fastness	EN ISO 105-B02	≥ 6

The above information is subject to modification for the benefit of further improvement. (03/20).

According to the European Regulation N° 305/2011 for CE Marking, the Declaration of Performance n° 0019-001-DoP-2015-01 is available on our website www.tarkett.com

